



It is a new generation ultra-brine freezing tunnel (shower system) to achieve higher performance and efficiency in quick freezing processes.

A continuous tunnel with a production capacity from 1,500 to 6,000 kg/h.

MODEL	SHOWER 3000	SHOWER 4000	SHOWER 5000
<b>GENERAL FEATURES</b>			
BRINE CONTROL SYSTEM			
ISOTHERMICAL CONTAINER			
HIGH STRENGTH FLOOR			
STAINLESS STEEL CONVEYOR			
REGULABLE SPEED OF CONVEYOR			
STAINLESS STEEL CONSTRUCTION			
AUXILIAR AGITATOR			
SUBMERGED HEAT EXCHANGER			
IP-65 ELECTRICAL PROTECTION			
EXTERNAL CALIPHUGATION IN TANK			
SAFETY LIGHTING			

SAL-SHOWER					
PRODUCTION	COOLING POWER NEEDS			EVAPORATION T°C	DIMENSIONS
Kcal/h.	Kcal/h.	Kw.	T.R.	°C	mm.
3000	290.000	337	96	-25	12.300
4000	385.000	448	127,3	-25	13.390
5000	475.000	552	157	-25	13.390

(\* ) Dimensions and powers are generic and susceptible to modifications according to real needs.

